

Materials

Front Projection

- FireHawk G4
- StudioTek 130 G3
- StudioTek 100
- UltraMatte 130
- UltraMatte 150
- Silver 3D
- Silver 5D
- Neve
- Tiburon G2
- GrayHawk RS G3

Rear Projection

- AeroView 70
- AeroView 100
- LumiFlex 130
- FilmScreen 100
- FilmScreen 150

Glass Rear Projection

- StarGlas 60
- StarGlas 100
- AeroGlas 70

LumiGlas 130



LumiGlas 130 is a glass rear projection screen material formulated for larger scale single projector installations. LumiGlas 130 is used in many business applications and is ideal for data, video, film, and power point presentations where ambient light is controllable. It provides a wide viewing angle for wide seating plans.

FEATURES:

- Superb white field uniformity
- High level of soundproofing between the projector and the audience area
- Identical gain and color matching for multiple screen applications

Material Type	Glass Rigid Rear Screen
Gain	1.3
Half Gain	42 degrees
Minimum Throw Distance	1.3 x image width
Ambient Light Front Reflectance Value	25% per foot candle
Ambient Light Resistance	Controlled lighting is recommended
Edge Blending Properties	Not recommended
Lay Flat Quality	Excellent
Flame Resistance	Yes
Size Limitations	130" x 240"
Material Thickness	1/2"
Screen Models	Rigid frames and multi-masking systems